



We WIRE for nearly any BRAND

The ESM8/HSM8 super lightweight design makes wearing the microphone more comfortable, even for long periods of time, without using excessive pressure to hold the microphone in place. The soft microphone stem allows for easy adjustment of the microphone's position as you wear the headset. These Headset microphones works great with many wireless transmitters available. The ESM8 & HSM8 can be wired to work with transmitters made by Galaxy Audio® Shure®, Sennheiser®, AKG® Audio Technica® and many others.

ESM8 **HSM8** ESM8 & HSM8 Elements 1.5mm OMNI ELEMENT 7mm UNI ELEMENT

- Hooks Around One Ear
- Flexible for Easy Formation
- 4" Mic Boom Length (Omni)
- 4.7" Mic Boom Length (Uni)
- 3.5 mm Mic Diameter (Omni)
- 7 mm Mic Diameter (Uni)
- Condenser Element
- · Freq. Response: Omni..20Hz-20kHz Uni.....50Hz-16kHz
- Detachable Cable





Black Beige

- Hooks Around Both Ears
- Flexible for Easy Formation
- 1.2" 7 Adjustable Mic Boom Length (Omni)
- 2" 7.9" Adjustable Mic Boom Length (Uni)
- 3.5 mm Mic Diameter (Omni)
- 7 mm Mic Diameter (Uni)
- Condenser Element
- · Freq. Response: Omni..20Hz-20kHz
 - Uni.....50Hz-16kHz
- Detachable Cable





Beige Black









ESM8/HSM8

Specifications

ESM8

Polar Pattern: Uni-Drectional/Omni Directional **Frequency Response (Omni):** 20 Hz - 20 kHz **Frequency Response (Uni):** 50 Hz - 16 kHz

Impedance (Omni): 1,800 Ohms Impedance (Uni): 1,000 Ohms Sensitivity (Omni): -65 dB re. 8mV/PA Sensitivity (Uni): -67 dB re. 5mV/PA

Max SPL: 135 dB

Operating Voltage: 1.5 - 9 Vdc

Cable Length: 4' (1.22 m) x 1.5 Diameter, 1.5 mm Thick Detachable Cable

Mic Boom Length: (Omni) 4", (Uni) 4.7"

Element: (Uni) Diameter 3.5 mm, (Omni) Diameter 7 mm

Element Type: Black Electret Condenser

Included Accessories: Choice of 4 Cables, Cable Clip, Windscreen, and Manual

Color: Beige or Black

Weight Without Cable: (Omni) 0.1 oz (2.8 g), (Uni) 0.1 oz (2.9 g)

HSM8

Polar Pattern: Uni-Drectional/Omni Directional Frequency Response (Omni): 20 Hz - 20 kHz Frequency Response (Uni): 50 Hz - 16 kHz

Impedance (Omni): 1,800 Ohms Impedance (Uni): 1,000 Ohms Sensitivity (Omni): -65 dB re. 8mV/PA Sensitivity (Uni): -67 dB re. 5mV/PA

Max SPL: 135 dB

Operating Voltage: 1.5 - 9 Vdc

Cable Length: 4 (1.22 m) x 1.5 Diameter, 1.5 mm Thick Detachable Cable Mic Boom Length: (Omni) 1.2" - 7" Adjustable, (Uni) 2" - 7.9" Adjustable


Element: (Uni) Diameter 3.5 mm, (Omni) Diameter 7 mm


Element Type: Black Electret Condenser


Included Accessories: Choice of 4 Cables, Cable Clip, Windscreen, and Manual

Color: Beige or Black

Weight Without Cable: (Omni) 0.18 oz (5.1 g), (Uni) 0.18 oz (5.2 g)











Specifications subject to change without notice.