

ANY SPOT[®] DIGITAL

PLUG & PLAY WIRELESS IN-EAR MONITOR SYSTEM

ASD-700

Galaxy Audio ASD-700 Digital UHF Plug & Play Wireless In-Ear Monitor System

The Galaxy Audio ASD-700 is a compact, easy-to-use Digital UHF Wireless In-Ear Monitor System designed for musicians and performers who prioritize mobility, clarity, and hearing protection. This affordable in-ear monitor system is ultra-portable, fitting in the palm of your hand, yet powerful enough to provide a clear, customized mix, perfect for live performances on any stage. With 150 feet of range and 15 selectable UHF channels, this powerful system allows musicians to create a personal mix they can clearly hear, enhancing overall stage performance.

Ideal for any stage performer—from vocalists to instrumentalists—the ASD-700 eliminates the need for traditional stage monitors, decreasing overall stage volume and protecting hearing while delivering a precise personal mix. Designed to minimize vocal strain and enhance clarity, this system enables performers to hear every note and beat accurately, offering clear sound without overexposure to loud stage volumes. The digital 24-bit/48kHz sample rate ensures pristine audio quality, and the system's frequency response spans from 20Hz to 20kHz, capturing the full range of musical dynamics.

The ASD-700's transmitter is compact and easy to manage, featuring essential controls for channel selection, input sensitivity, and a clear display for channel, frequency, and battery status. Paired with a lightweight bodypack receiver, this system allows up to eight hours of uninterrupted performance, ensuring stability through long sets. Included with the ASD-700 are the EB5 earbuds, an XLRM to 1/4" adapter, a dual USB-C charging cable, a USB power block, and a semi-hard case, giving you everything you need to get started right out of the box.

Backed by Galaxy Audio's 3-Year Warranty, the ASD-700 is not just a monitor system; it's an investment in your music career, providing peace of mind and exceptional audio quality for every performance.

ASD-700

- 150 Foot Range
- Easy Plug & Play IEM System
- 15 Channel Digital UHF Wireless
- Crystal-clear audio with 24-bit/48kHz resolution for professional sound quality
- Works with Earbuds or Headphones. High Definition Earbuds Included.
- Ultra-Compact Design
- Affordable and Durable
- Up to 8-Hour Battery
- 3-Year Warranty*

Also available in Twin Packs & Band Packs

ASD-700-2 Twin Pack



ASD-700-4 Band Pack



Case Included



*(3-Year Warranty Applies to ASD-700 Transmitter & Receiver Only)

AMPLIFY YOUR PASSION.



ANY SPOT[®] DIGITAL

PLUG & PLAY WIRELESS IN-EAR MONITOR SYSTEM

ASD-700

Specifications: ASD-700 System

Band: UHF

Frequency: 15 Channels. Frequency CODE B5 550-569MHz, Frequency CODE B6 571-585MHz

Transmission: Mono

Sample Rate: 24bit/48kHz

Operating Range: Under Typical Conditions 150' (45m)

Note: actual range depends on RF signal absorption, reflection, interference, and battery characteristics

Audio Frequency Response: +/-3dB 20Hz~20kHz

Dynamic range: 101dB

S/N: 98.d dB

Latency: 5.8ms

Operating Temperature Range: 14°F to 122°F (-10° C to +50° C) **Note:** battery characteristics may limit this range

ASD-700T Transmitter

Transmitter Output Level: 10 mW

Max Audio Input Level: Aux +10dBu, Line +19dBu

Controls: Power, channel select, input sensitivity

Display: Channel, frequency, battery level

XLR Input: Impedance balanced

Pin: 1 Ground (cable shield)

Pin: 2 Audio +

Pin: 3 No Audio -

Dimensions: 1.73" x 8.34" x 3.77" (105 x 35 x 25 mm)(HxWxD)

Weight: 19.75 oz (560 g)

Power Supplied By: 3.7V 800mA Lith-Ion internal battery

Battery Life: Up to 8 hours

ASD-700R Body Pack Receiver

Audio Output Level: 50mW

Output Connector: 1/8" (3.5mm) Stereo Earphone Connector

Controls: Power, Volume, Channel Up/Down

Display: Channel, frequency, RF level, battery level

Dimensions: 3.54" x 2.51" x 0.9" (90 x 64 x 23 mm)(HxWxD)

Weight: 3.35 oz (95 g)

Power Supplied By: 3.7V 1000mA Lith-Ion internal battery

Battery Life: Up to 8 hours



**ASD-700T
Transmitter**



**ASD-700R
Receiver**

Includes the following components:

ASD-700T Transmitter

ASD-700R Receiver

EB5 Earbuds with Soft Carry Pouch

Dual USB-C charge cable

USB Power Block

XLRM to 1/4" Adapter

Soft Shell Semi Hard Zip Case

Quick Start Guide



FREQUENCY CODES

CODE B5 550-569 MHz

CODE B6 571-585 MHz

**UHF
BAND**



Specifications subject to change without notice.



AMPLIFY YOUR PASSION[™]

601 E. Pawnee Wichita, KS 67211 316. 263.2852 FAX 316.263.0642 www.galaxyaudio.com

Distributed in Canada by ADIprou.ca 1275 Newton, unit 6 Boucherville, QC J4B 5H2 Canada
450.449.8177 FAX 450.449.8180

V20250105