

# Galaxy Audio HLM4 and HLM8 Hairline/Lavalier Performer Series Microphones

Galaxy Audio's HLM4 and HLM8 Hairline Microphones deliver professional audio quality in ultra-discreet, easy-to-conceal designs. Engineered for theatre, presentations, interviews, and live events, these versatile omnidirectional microphones can be positioned along the hairline or on costumes, seamlessly blending into any setting. The 5mm HLM4 offers an affordable, reliable option for those seeking quality sound, while the 3.5mm HLM8 provides nearly invisible placement with a broad 20Hz-20kHz frequency response for high-fidelity audio capture.

Both models come equipped with four detachable cables compatible with major wireless systems, including Galaxy Audio®, Shure®, Sennheiser®, AKG®, and Audio Technica®, allowing easy integration with existing setups. A shirt clip and windscreen are included for flexibility in placement and enhanced audio clarity. Whether used as a hairline or lavalier mic, these microphones deliver crystal-clear sound while remaining hidden from view—perfect for stage, broadcast, and public speaking.

#### **Key Features:**

- HLM4: 5mm diameter, 85Hz-15kHz frequency response
- HLM8: 3.5mm diameter, 20Hz-20kHz frequency response
- Omnidirectional condenser elements for natural, consistent audio capture
- Broad compatibility with 4 detachable cables for popular wireless systems
- Flexible placement options with included shirt clip and windscreen









Available cables wired for:

CBLAT - AUDIO-TECHNICA® (HIROSE cW 4 PIN)

CBLATCH - GEN 2 cH AUDIO-TECHNICA® (HIROSE cH)

CBLEV - EV® & TELEX® (TA4F)

CBLAKG - GALAXY AUDIO® /ÁKG® (TA3F)

CBLSEN - SENNHEISER® (3.5mm)

CBLSHU - SHURE® (TA4F)

MIXED - GALAXY®/AKG®, SHURE®, AT® & SENN®







### **HLM4** Specifications:

Length: 13-Inch from Mic Capsule to Cable Connection

Element: Diameter 5 mm

Element Type: Back Electret Condenser

Polar Pattern: Omni Directional

Frequency Response (Omni): 85 Hz - 15 kHz Impedance: 2,200 Ohms ± 30% (at 1 K Hz)

Sensitivity: -40dB re.1V/Pa

Max SPL: 110 dB


Operating Voltage: 2.0 - 10 Vdc

Detachable Cable Length: 4' (1.22 m) x 1.5 Diameter, 1.5 mm Thick Detachable Cable

Included Accessories: Choice of 4 Cables, Windscreen, and Manual

Color: Beige or Black

Weight Without Cable: 0.09 oz (2.6 g)









## 3.5 mm Element HLM8

## **HLM8** Specifications:

Length: 13-Inch from Mic Capsule to Cable Connection

Element: Diameter 3.5 mm

Element Type: Back Electret Condenser Polar Pattern: Omni Directional Frequency Response: 20 Hz - 20 kHz Impedance: 1.8kΩ ± 30% (at 1 K Hz)


Sensitivity: 8mV/Pa Max SPL: 135 dB

Operating Voltage: 1.5 - 9 Vdc

**Detachable Cable Length:** 4' (1.22 m) x 1.5 Diameter, 1.5 mm Thick Cable **Included Accessories:** Choice of 4 Cables, Cable Clip, Windscreen, and Manual

Color: Beige or Black

Weight Without Cable: 0.08 oz (2.3 g)





#### LIMITED ONE YEAR WARRANTY

Please visit galaxyaudio.com for the latest updates

Specifications subject to change without notice.



601 E. Pawnee Wichita, KS 67211 316. 263.2852 FAX 316.263.0642 www.galaxyaudio.com